(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Guinama base 96 alcohol

Product Code: 10920

1.2 Relevant identified uses of the substance or mixture and uses advised against.

industrial cosmetic use

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **GUINAMA**Address: C/ Oslo N°3

City: 46185 La Pobla de Vallbona

Province: Valencia

Telephone: +34961869090 / 902119816

Fax: +34961850352 E-mail: ventas@guinama.com Web: www.guinama.com

1.4 Emergency telephone number: +34961869090 / 902119816 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Eye Irrit. 2: Causes serious eye irritation.

Flam. Liq. 2: Highly flammable liquid and vapour.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:





Signal Word:

Danger

Hazard statements:

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges. P264 Wash ... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Version 1 Date of compilation: 20/12/2021 Page 2 of 11
Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use... to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to ...

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-002- 00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01- 2119457610-43-XXXX	ethanol, ethyl alcohol	10 - 100 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

^[2] Substance with a national workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Date of compilation: 20/12/2021 Version 1

Page 3 of 11 Revision date: 04/09/2023 Print date: 04/09/2023 **Version 6 (replaces version 5)**

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture. Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking, Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Date of compilation: 20/12/2021 Version 1

Page 4 of 11 **Version 6 (replaces version 5)** Revision date: 04/09/2023 Print date: 04/09/2023

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 15 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Inhalation, Chronic, Systemic effects	950
	(Workers)		(mg/m³)
	DNEL	Inhalation, Chronic, Systemic effects	114
	(Consumers)		(mg/m³)
	DNEL	Dermal, Chronic, Systemic effects	343
	(Workers)		(mg/kg
			bw/day)
	DNEL	Dermal, Chronic, Systemic effects	206
ethanol, ethyl alcohol	(Consumers)		(mg/kg
CAS No: 64-17-5			bw/day)
EC No: 200-578-6	DNEL	Inhalation, Chronic, Local effects	1900
200 370 0	(Workers)		(mg/m3)
	DMEL	Inhalation, Short term, Local effects	950
	(Consumers)		(mg/m3)
	DMEL	Oral, Chronic, Systemic effects	87 (mg/kg)
	(Consumers)		
	DMEL	Inhalation, Chronic, Systemic effects	114
	(Consumers)		(mg/m3)
	DMEL	Dermal, Chronic, Systemic effects	206
	(Consumers)		(mg/kg)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
ethanol, ethyl alcohol	aqua (intermittent releases)	2,75 (mg/L)
CAS No: 64-17-5	Soil	0,63 (mg/kg
EC No: 200-578-6		soil dw)
	sediment (freshwater)	3,6 (mg/kg
		sediment dw)

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Version 1 Date of compilation: 20/12/2021 Page 5 of 11
Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

STP	580 (mg/L)
sediment (marine water)	2,9 (mg/kg
	sediment dw)
oral	0,38 (g/kg
	food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %					
Uses:	industrial cosmetic use					
Breathing protect						
PPE:	Filter mask for protection against gases and particles.					
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.					
CEN standards:	EN 136, EN 140, EN 405					
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach					
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer. A2					
Filter Type needed: Hand protection:	AZ					
PPE:	Protective gloves.					
Characteristics:	«CE» marking, category II.					
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420					
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.					
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.					
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35					
Eye protection:						
PPE: Characteristics:	Face shield. «CE» marking, category II. Face and eye protector against splashing liquid.					
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.					
Characteristics: CEN standards:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move					
Characteristics: CEN standards: Maintenance: Observations: Skin protection:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm					
Characteristics: CEN standards: Maintenance: Observations:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing.					
Characteristics: CEN standards: Maintenance: Observations: Skin protection:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE:	 «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE: Characteristics:	 «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. 					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE: Characteristics: CEN standards: Maintenance: Observations:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE: Characteristics: CEN standards: Maintenance: Observations: PPE:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. Anti-static safety footwear.					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE: Characteristics: CEN standards: Maintenance: Observations:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.					
Characteristics: CEN standards: Maintenance: Observations: Skin protection: PPE: Characteristics: CEN standards: Maintenance: Observations: PPE:	«CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. Anti-static safety footwear.					

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Page 6 of 11

Date of compilation: 20/12/2021 Version 1

Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

The level of comfort during use and acceptability are factors that are assessed very differently depending Observations:

on the user. Therefore, it is advisable to try on different footwear models and, if possible, different

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Colourless

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: 12 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable/Not available due to the nature/properties of the product

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: Not applicable/Not available due to the nature/properties of the product Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Date of compilation: 20/12/2021 Version 1

Page 7 of 11 **Version 6 (replaces version 5)** Revision date: 04/09/2023 Print date: 04/09/2023

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity				
Name	Туре	Test	Kind	Value	
		LD50	Rat	7060 mg/kg bw [1]	
		LD50	mouse	3 450 mg/kg bw [2]	
	Oral	[1] Toxicology and Applied Pharmacology. Vol. 16, Pg. 718, 1970			
ethanol, ethyl alcohol		[2] Publica (1992) loc.	g. Sanit. 32, 31. cited in RTECS		
		DL50	Rabit	20000 mg/Kg (-) [1]	
	Dermal	F43			
		[1] -	D. I	1247 // /41 \ [17	
	Inhalation	CL50	Rat	124.7 mg/L (4h) [1]	
CAS No: 64-17-5 EC No: 200-578-6	Imaduon	[1] -			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Туре	Test	Kind	Value

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Version 1 Date of compilation: 20/12/2021 Page 8 of 11
Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

			LC50 Fish 11000 mg/l (96 h) [1]
		Fish	[1] Bengtsson, B.E., L. Renberg, and M. Tarkpea 1984. Molecular Structure and Aquatic Toxicity - an Example with C1-C13 Aliphatic Alcohols. Chemosphere 13(5/6):613-622
ethanol, ethyl alcohol		Aquatic invertebrates	LC50 Crustacean Crustacean Grustacean Crustacean Grustacean Geriodaphnia Geriodaphnia dubia Sol 2 mg/l (48 h) [2] Sol 2 mg/l (48 h) [3] Sol 2 mg/l (48 h) [2] Sol 2 mg/l (48 h) [3] Sol 2 mg/l (48 h) [3] Sol 2 mg/l (48 h) [2] Sol 2 mg/l (48 h) [3] Sol 2 mg/l (48 h)
CAS No: 64-17-5	EC No: 200-578-6	Aquatic plants	

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
ethanol, ethyl alcohol		-0,31	o.	_	Very low
CAS No: 64-17-5	EC No: 200-578-6	-0,31	3	-	very low

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading **Air:** Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1170

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1170, ETHANOL (ETHYL ALCOHOL), 3, PG II, (D/E) IMDG: UN 1170, ETHANOL (ETHYL ALCOHOL), 3, PG II ICAO/IATA: UN 1170, ETHANOL (ETHYL ALCOHOL), 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

14.6 Special precautions for user.

Labels: 3



Hazard number: 33

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 1 L

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Version 1 Date of compilation: 20/12/2021 Page 10 of 11
Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

IMDG LQ: 1 L ICAO LQ: 1 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Changes in the composition of the product (SECTION 3.2).
- Modification of the information of the stability and reactivity conditions (SECTION 10.2).
- Modification of the information of the stability and reactivity conditions (SECTION 10.3).
- Modification of the information of the stability and reactivity conditions (SECTION 10.4).
- Modification of the information of the stability and reactivity conditions (SECTION 10.5).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
64-17-5	ethanol, ethyl alcohol	Registered

(in accordance with Regulation (EU) 2020/878)

10920-Guinama base 96 alcohol



Version 1 Date of compilation: 20/12/2021 Page 11 of 11
Version 6 (replaces version 5) Revision date: 04/09/2023 Print date: 04/09/2023

Risk classification system NFPA 704:



Health hazard: 2 (Hazardous)

Flammability: 4 (Below 73°F)

Reactivity: 0 (Stable)

Abbreviations and acronyms used:

ADR/RID: Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.